



M/Connect[™] 2

Humanscale[®]

M/CONNECT 2 is a next-generation USB docking station that keeps all your devices connected through a single hub of power and data. With a patented split dock design, M/Connect 2 provides multiple connection options beneath the desk while keeping all essential ports above the work surface and conveniently within reach.

- Universal USB docking station with USB-C, USB-A and Thunderbolt connectivity
- Backwards compatible to USB-A
- 100W power delivery
- Supports 4K video resolution for up to 2 monitors
- Features a total of 11 ports for power and data
- Features two charging ports dedicated exclusively to delivering power, alleviating potential security risks
- Various mounting options available for easy application to any worksurface
- Color Options: Polished Aluminum with White Trim, Silver with Gray Trim, Black with Black Trim
- Kensington Security Lock Slot available for both the hub and dock for additional security and theft protection
- Limited 3-year warranty

*Also available as a
Stand Alone Split Dock
(No Monitor Arm)*



A TOTAL OF 11 CONNECTIONS

Desktop Hub

- 2 USB-A data ports
- 1 USB-C charging port
- 1 USB-A charging port
- 1 3.5 mm Audio/microphone

Underdesk Dock

- 3 USB-A data ports (1, high charging port)
- 2 Display Ports
- 1 Ethernet Jack



Removable top hub allows part replacement and upgrade without disassembling monitor arm setup

DESIGN STORY

For more than 35 years, Humanscale has been creating solutions that enhance the computing experience. Our products are designed to make the workstation a more effective tool for the use of today's technology. With M/Connect 2, we have applied our expertise and experience to the USB docking station. Our split dock design, which can be used with or without a monitor arm, eliminates desktop cable clutter, increases usable workspace, and enhances user performance.

Without M/Connect 2



With M/Connect 2



SPECIFICATIONS				
Desktop Dock	USB ports	USB-C full feature with PD charging 100W		
	USB ports — data and charging	2x USB-A 3.1 (5V,0.9A max)		
	USB ports — charging only, no data communication	USB-C (5V, 3.0A max) USB-A (5V, 2.4A max)		
	Microphone/Headphone	3.5mm combo jack		
Underdesk Dock	Without HDCP enabled	4k 3840x2160 p60 4096x2160 p60	2k 2560x1600 p60 2560x1440 p60	1k FHD
	Video 1 output DisplayPort++ (Dual mode DP1.2)	✓	✓	✓
	Video 2 output DisplayPort++ (Dual mode DP1.2)	✓	✓	✓
	Network	Gigabit Ethernet Transfer rate 10Mbit/100Mbit/1Gbit		
	USB ports	2x USB-A 3.1 (5V, 0.9A max) 1x USB-A 3.1 with charging (5V, 2.4A)		
Operating System	Windows 7/7Pro (32bit/64bit), Windows 8.1/8.1Pro (32bit/64bit), Windows 10 (32bit/64bit), Apple OS X Android Chrome Ubuntu			
Environment	Temperature - Operating	0°C to 40°C		
	Temperature – non-Operating	-20°C to 60°C		
	Relative Humidity – Operating	10% to 80% (non-condensing 5 to 35°C)		
	Relative Humidity – non-Operating	5% to 90% (non-condensing -20 to 60°C)		
	Altitude – Operating	Sea level to 5000m		
	Altitude – non-Operating	5000m		
	Designed to meet RoHS and WEEE directives			
Dimensions	Desktop Dock	150mm (w) x 150mm (d) x 22.5mm (h)		
	Underdesk Dock	191mm (w) x 90mm (d) x 23mm (h)		
Weight	2.1 kg (dock and hub)			
AC Adapter	Input Voltage	90 – 264V (47-63Hz)		
	Output Voltage	20V (+/- %), 9A, 180W		
	Efficiency	Meets US DoE VI		
Accessories Included	1x USB-C full feature cable - 1.0m in long with USB-C to USB-A adapter attached, and cable retainer			